



# MAXFLO AASHTO DUAL WALL PIPE

12", 15", 18", 24" HDPE PIPE

30", 36", 48" HDPE PIPE



## DUAL WALL FEATURES

- In-Line Bell Design with ASTM F477 gaskets
- High performance bell/spigot for superior connective strength
- All MaXflo bells cover a minimum of two ribs
- All pipe and fittings meet or exceed AASHTO M252S and M294S

*TIMEWELL MaXflo Pipe meets or exceeds numerous industry standards including:*

<b>AASHTO M252</b>	<b>Requirements and testing for 3"-10" pipe, couplings and fittings</b> for use in subsurface drainage systems, storm sewers, and in surface drainage Referenced - ASTM D618 - ASTM D3350 - ASTM D2122 - ASTM F405 Standards: - ASTM D883 - ASTM D1693 - ASTM D2412 - ASTM F412
<b>AASHTO M294</b>	<b>Requirements and testing for 12"-60" pipe, couplings and fittings</b> for use in surface and subsurface drainage applications Referenced - ASTM D618 - ASTM D3350 - ASTM D2122 - ASTM D2412 Standards: - ASTM D883 - ASTM D1693 - ASTM D2444 - ASTM F667 - AASHTO Standard Specification for Highway Bridges
<b>ASTM F405</b>	<b>Requirements and testing 3"-6" pipe and fittings</b> for materials, marking dimensions, workmanship, elongation, brittleness, pipe stiffness, and perforations
<b>ASTM F667</b>	<b>Requirements and testing for 8"-24" pipe and fittings</b> for materials, workmanship, dimensions, perforations, pipe stiffness, elongation, joint separation resistance, quality of extrusion, brittleness, bond, and markings
<b>ASTM D3350</b>	<b>Identification of pipe and fitting materials</b> in accordance with a cell classification system
<b>ASTM D2321</b>	<b>Recommendations for the installation of pipe</b> used in sewers and other gravity-flow applications
<b>ASTM D3212</b>	<b>Specifications for joints of pipe systems</b> intended for drain, and gravity sewerage at internal or external pressures less than 25 ft head using flexible watertight elastomeric seals
<b>ASTM F477</b>	<b>Requirements for elastomeric seals (gaskets)</b> used to seal the joints of pipe used for gravity, low-pressure, and high-pressure applications
<b>ASTM F2306</b>	<b>Requirements for non-pressure (gravity flow) 8"-60" annular corrugated profile-wall polyethylene (PE) pipe and fittings for gravity-flow storm sewer and subsurface drainage applications</b>
<b>NTPEP</b>	<b>National Transportation Product Evaluation Program Certified:</b> Certification Program of AASHTO (4"-60")